# **Technical Data Sheet**

TDS B7768 SILICONE PTFE Revised 03.08.10



# **Bondloc B7768 Silicone PTFE**

# PRODUCT DESCRIPTION

B7768 is ideal for a multi-purpose, multifunctional light grease application. A basic grease enriched with silicone and PTFE to reduce friction and improve the lubricity of the grease, producing a very high performance lubricant grease.

#### **APPLICATIONS**

Silicone PTFE has been designed for use on hinges, brushes and pivot points to ensure smooth operation and protection from moisture and other elements. Improved protection and durability are given by the silicone and PTFE resulting in a better level of performance under greater stress than standard grease.

#### **USEFUL HINTS**

- Reduces friction
- Improves protection
- High performance lubricant

#### INSTRUCTIONS FOR USE

Spray onto the surface from a distance of 10-20 cm. For more detailed application use the extension tube, to spray directly onto or into the desired component.

#### **TECHNICAL FEATURES**

Physical state	400ml aerosol
Appearance	Light covered foamy liquid
Odour	Mild solvent
Auto flammability	unknown for blend >200°C
Can pressure	3.5 bar

#### **STORAGE**

Storage temperature should be kept below 50°C. Storage area should be out of direct sunlight.

# **HEALTH & SAFETY IN USE**

Pressurised container. Protect from sunlightanddonotexposetotemperatures exceeding 50°C. Do not pierce or burn, even after use. Do not spray on an open flame or any incandescent material. Keep away from sources of ignition.

See MSDS for full details.

### **PRESENTATION**

Aerosol......200ml,400ml