Material Safety Data Sheet

MSDS B7768 SILICONE PTFE Revised 03.08.10



1: IDENTIFICATION OF THE SUBSTANCE/ PREPARATION AND COMPANY / UNDERTAKING

PRODUCT NAME: Bondloc B7768 **MANUFACTURER**: Bondloc UK Limited,

Bewdley,

Worcestershire DY12 2TZ

Emergency Info: +44 (0)1299 269 269

2: COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous components	CAS	Risk phrase	Range
Grease			10-30%
Silicone oil	63148-62-0		<10%
PTFE blend			<10%
Aliphatic hydrocarbon	64724-49-0	R45,65	10-20%
Butane	106-97-8	F, R12	10-30%
Propane	74-98-6	F, R12	10-30%

3: HAZARDS IDENTIFICATION

Most important hazard Highly flammable.

4: FIRST-AID MEASURES

This is an aerosol product use only in well ventilated areas. The contents are flammable and maybe harmful by deliberate prolonged inhalation or ingestion. Hydrocarbon propellant is a asphyxiant if there is insufficient ventilation. This would constitute abuse of the product. Always wash hands after use. Repeated exposure may cause skin dryness or cracking. Keep in a safe place away from children. Flammable pressurised container protect from sunlight and do not expose to temperatures exceeding 50°C. Do not spray onto a naked flame or any incandescent material, hot surface or unprotected electrical equipment. Do not breathe the spray mist. Vapours may cause drowsiness and dizziness. Do not spray near eyes, irritating to eyes. Always read container warnings.

General

In all cases of doubt or when symptoms persist seek medical attention. Never give anything by mouth to an unconscious person.

First Aid for Inhalation:

Remove to fresh air, keep warm and at rest. If breathing is irregular or stopped give artificial respiration. Give nothing by mouth. If unconscious place in recovery position and seek medical advice.

First Aid for Skin Contact:

Remove contaminated clothing. Wash skin thoroughly with soap and water or use a proprietary skin cleaner. Do not use solvents or thinners. Avoid sunlight or other sources of UV radiation.

First Aid for Eye Contact:

Contact lenses should be removed. Irrigate copiously with clean, fresh water for at least 10 minutes holding the eyelids apart, seek medical advice.

First Aid for Ingestion:

If accidentally swallowed obtain immediate medical attention. Keep at rest. DO NOT induce vomiting.

MSDS B7768 Page 2 of 4

5: FIRE-FIGHTING MEASURES

Extinguishing Media: Carbon Dioxide, BCF, Dry powder, sand or earth.

For larger fires use foam, water fog or spray and avoid contamination.

Positive pressure breathing apparatus should be used.

6: ACCIDENTAL RELEASE MEASURES

Initial spillage would be flammable. Spillage is unlikely in large quantities with an aerosol product. Keep damaged containers away from sources of ignition and in well ventilated areas. Contents may cause staining and it should be expected that marks will not be able to be removed.

Environmental precautions

In the concentrations within 1-1000 cans the components would not present an environmental hazard as most of the product would quickly evaporate, leaving only the residue.

Cleaning

In small quantities any liquid should be absorbed into a suitable media, such as sand and disposed of safely. The residue should be washed away with soapy water, though staining should be expected.

7: HANDLING AND STORAGE

Handling Handle carefully, in general handling aerosols should not be considered as hazardous.

Storage Always store aerosols away from sources of heat, including direct sunlight and in dry conditions.

Avoid extremes of temperature and moisture. A stable, cool, dry ambient environment is most suitable. Avoid contamination with other products. The containers will not last indefinitely even when stored in a cool dry area, they should be inspected periodically during long-term storage.

Note container warnings.

8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Supplier recommends 600ppm total hydrocarbon based on composition. As with all aerosols, the products should only be used in well-ventilated areas, but responsible use is not potentially harmful.

Respiratory protection

if ventilation is not possible, then suitable respiratory protection is essential if there is a risk of solvent vapour concentrations. Use organic/inorganic vapour filters. Vapours may cause drowsiness or dizziness.

Hand protection

repeated exposure may cause skin cracking or dryness, gloves may be required.

Eye Protection

Goggles.

Skin Protection

Wear protective clothing covering arms and legs.

9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance	White frothy grease	
Odour	Mild solvent	
Melting point	>-30°C	
Flash point	>20°C	
Flammability	Highly flammable liquid	
Relative density	0.85Kg/m3	
Solubility	Insoluble in water	

MSDS B7768 Page 3 of 4

10: STABILITY AND REACTIVITY

The container is inherently stable under instructed conditions for a reasonable period of time (at least 24-36 months).

Avoid extremes of temperature, including direct sunlight and extreme freezing. Avoid exposure to moisture, which may cause container deterioration and pH, where acidity may damage container integrity. Avoid sudden impacts, which may damage container integrity. Avoid contact with water, acids and high temperatures.

Container corrosion may occur with time and damaged containers should be disposed of before any danger is evident. Flammable, liquid contents should be considered generally not reactive.

11: TOXICOLOGICAL INFORMATION

This is designed for external use only. Essentially, when used in this aerosol form, there are no potential toxic effects. The data is as follows:

Aliphatic hydrocarbon No data available on the product

Butane/Propane Occupational exposure standard is 600ppm (1430 mgm)

Used correctly in aerosol form, all components can be considered to have a low order of toxicity (LD50 oral rat 500mg/kg, skin 3000mg/kg). Deliberate inhalation may cause severe pulmonary and breathing difficulty, dizziness, drowsiness (narcosis) and headaches (but this is unlikely in normal usage), and would constitute abuse.

Skin and eye irritation may result from continued exposure to vapors when used in areas of poor ventilation, or when working in close proximity to the spray for prolonged periods, and suitable steps should be taken to avoid such conditions.

Constituent products have shown no conclusive carcinogenic or mutagenic effects in long term tests.

12: ECOLOGICAL INFORMATION

This relates to the contents only, see Disposal.

The product will evaporate quickly to the air. A thick white liquid, easily absorbed, will evaporate and leave a sludge. The sludge will present no other significant hazards, with no dangerous products arising from degradation. Mobility will be slow.

Degradation will be relatively slow though ultimately almost complete.

Accumulation is unlikely once physical breakdown commences.

Short and long term effects should not be considered significant. Very short term damage to aquatic and soil organisms may occur in large spillage (1000+ containers) though this should disperse quickly (especially if absorbent material is used). No effects on plants or animals are indicated. There is no ozone depletion, ozone creation or global warming potential. Water treatment plants would not be affected by small to medium volumes of this material.

13: DISPOSAL CONSIDERATIONS

The container should be totally discharged and disposed of as hazardous waste. SEE CONTAINER WARNINGS. I.e. do not puncture or incinerate/burn, even after use. Dried material is non-hazardous.

14: TRANSPORT INFORMATION

UN NUMBER: UN 1950

IMDG page 2120

HAZARD CLASS: 2.1 For Sea Transport.

UK TRANSPORT DESCRIPTION: FLAMMABLE AEROSOLS LIMITED QUANTITIES(capacity less than 1 litre).

UK TRANSPORT CLASSIFICATION: MISCELLANEOUS GOODS

MSDS B7768 Page 4 of 4

15. REGULATORY INFORMATION LABELLING

The COSHH Regulations apply in the UK.

The CHIP Regulations apply in the UK.

The Environmental Protection Act Regulations apply in the UK.

SYMBOLS: F+

RISK/SAFETY PHRASES:

F+ Flammable. Keep out of reach of children. Protect from sunlight and do not expose to Temperatures exceeding 50 °C. Do not pierce or burn, even after use. Do not spray onto a naked flame or any incandescent material. (Aerosol safety phrases).

R45,65 May cause cancer, harmful - may cause lung damage if swallowed

\$53,56 Avoid exposure – obtain special instructions before use, dispose of container to hazardous or special waste collection point

R12 Extremely flammable

16: OTHER INFORMATION

This is an aerosol product and should be used carefully.

It represents no greater dangers than any other aerosol product and all regulations applicable are general industry guidelines. The marks are non-penetrating and non-harmful.

The information included is all that available for the component products at this time.

The information contained in this Safety Data Sheet does not constitute the user's own assessment of the workplace risks as required by other health& safety legislation.

The provisions of the Health & Safety at work etc. Act and the Control of Substances Hazardous to Health Regulations apply to the use of this product at work.

PRECAUTIONS: This product and the auxiliary materials normally

combined with it are capable of producing adverse health effects ranging from minor skin irritation to serious systemic effects. None of these materials should be used, stored, or transported until the handling precautions and recommendations as stated in the Material Safety Data Sheets (MSDS) for this and all other products being used are understood by all persons who will work with the product.

Warranty: All products purchased from or supplied by Bondloc are subject to terms and conditions set out in the contract. Bondloc warrants only that its product will meet those specifications designated as such herein or in other publications. All other information supplied by Bondloc is consider accurate but are furnished upon the express condition the customer shall make its own assessment to determine the product's suitability for a particular purpose.

makes no other warranty, either express or implied, including those regarding such other information, the data upon which the same is based, or the results to be obtained from the use thereof; that any product shall be merchantable or fit for any particular purpose; or that the use of such other information or product will nor infringe any patent.