Technical Data Sheet

TDS B7774 BELT DRESSING

Revised 03.08.10



Bondloc B7774 Belt Dressing

PRODUCT DESCRIPTION

B7774 belt dressing is a blend of oils, acrylic polymers and additives are designed to prevent slippage of industrial belts and conveyors. The use of this product will help maintain belts in good condition preventing cracking and over heating.

USEFUL HINTS

Prevents belt/conveyor slippage. Impedes cracking and over heating. Rapid dry time. Promotes adhesion.

INSTRUCTIONS FOR USE

Shake can thoroughly before use. It should be sprayed from a distance of 25-30 cm. It should not be used where the use of lubrication is not recommended by the belt manufacturer.

PROPERTIES

It gives a colourless tacky resin/oil/solvent coating that rapidly dries. It will not yellow or oxidise, even over long periods, thus giving maximum service for life. The resultant coating lubricated the belt as well as promoting adhesion. This reduces wear caused by slipping and over heating.

TECHNICAL FEATURES

Physical state	400ml aerosol
Appearance	Colourless liquid
Odour	Solvent
Auto flammability	Unknown for blend >200°C
Can pressure	3.5 bar

STORAGE

Storage temperature should be kept below 50°C. Storage area should be out of direct sunlight.

HEALTH & SAFETY IN USE

Pressurised container. Protect from sunlightanddonotexposetotemperatures exceeding 50°C. Do not pierce or burn, even after use. Do not spray on an open flame or any incandescent material. Keep away from sources of ignition.

See MSDS for full details.

PRESENTATION

Aerosol......400ml